



Easy Texture Product Sheet

Product Description

Easy Texture is a proprietary powdered mixture of fine aggregates and white Portland cement. Performance Polymers Easy Texture is designed to be used with stencils, tapped patterns, or applied as a knock-down texture. This product can be applied as a skim coat or a spray texture. Also great for hand carved rock.

Note: Performance Polymers Easy Texture has no polymer content and requires the addition of Poly 600 co-polymer or Poly 686 dry co-polymer. Easy Texture with dry co-polymer is available.

Coverage Rate

Coverage will depend upon the porosity of the surface, and application procedure followed. This product will cover approximately 150 square feet per bag as a rough skim coat, approximately 200 square feet per bag as a smooth skim coat, and approximately 175 square feet as a medium spray texture.

Mixing Instructions

Performance Polymers Easy Texture mix is designed to require Performance Polymers Poly 600 co-polymer. Add 1.5 to 3 quarts of Poly 600 with 3 to 4 quarts of water per 50 lb bag depending on the application. Do not exceed 8 quarts per bag. Mix with a paddle mixer until mixture has thoroughly combined.

Primary Uses

This product eliminates concrete removal and can be used in virtually any climate. This product can be applied on interior and exterior applications. Performance Polymers Easy Texture is environmentally friendly.

Typical Applications

Interior and exterior floors, walkways, patios, amusement parks and casinos, pool decks, bridges, parking structures, driveways, one step tile set, slabs, curb and gutter repair, warehouse floors, waterproof retaining walls, leveling floors, and much more.

Important Notice to Purchaser

All products manufactured by Performance Polymers, LLC are made in the USA.

6185 S. Valley View Blvd. Ste N, Las Vegas, NV 89118

TO ORDER CALL: 800-983-6993 • Fax: 702-252-3423 • www.concreteoverlaypolymer.com

The information herein is general information designed to assist customers in determining whether our products are suitable for their applications. Our products are intended for sale to industrial and commercial customers. We require customers to inspect and test our products before use and to satisfy themselves as to contents and stability for their specific applications. We warrant that our products will meet our written specifications. Nothing herein shall constitute any other warranty expressed.